

Table of Contents


```
@InProceedings{REIS2020,  
  author="dos Reis, Alexandre Soares  
    and Gielen, Elien  
    and Wopereis, Ko  
    and Pasternak, Marcel  
    and Soo{"a"}{"a"}r, Vaido  
    and Schneider, Tobias  
    and Duarte, Abel J.  
    and Malheiro, Benedita  
    and Justo, Jorge  
    and Ribeiro, Cristina  
    and Silva, Manuel F.  
    and Ferreira, Paulo  
    and Guedes, Pedro",  
  editor="Silva, Manuel F.  
    and Lu{"i"}s Lima, Jos{"e"}  
    and Reis, Lu{"i"}s Paulo  
    and Sanfeliu, Alberto  
    and Tardioli, Danilo",  
  title="Smart Companion Pillow -- An EPS@ISEP 2019 Project",  
  booktitle="Robot 2019: Fourth Iberian Robotics Conference",  
  year="2020",  
  publisher="Springer International Publishing",  
  address="Cham",  
  pages="465--476",  
  abstract="This paper describes the design and development of a Smart  
Companion Pillow, named bGuard, designed by a multinational and  
multidisciplinary team enrolled in the European Project Semester (EPS) at  
Instituto Superior de Engenharia do Porto (ISEP) in the spring of 2019.  
Nowadays, parents spend most of the day at work and become naturally worried  
about the well-being of their young children, specially babies. The aim of  
bGuard is to provide a 24-hour remotely accessible baby monitoring service,  
contributing to reduce parenting stress. The team, based on the survey of  
related products, as well as on marketing, sustainability, ethics and  
deontology analyses, developed a remotely interactive Smart Companion Pillow  
to monitor the baby's health and room air quality. The collected data, once  
it is saved on an Internet of Things (IoT) platform, becomes remotely  
accessible. The bGuard pillow, thanks to its shape, reduces the risk of the  
baby rolling from back to tummy, lowering the risk of Sudden Infant Death  
Syndrome (SIDS).",  
  isbn="978-3-030-36150-1"  
}  
  
@article{LEE2018,  
  title = "Design and Implementation of Monitoring System Architecture for  
Smart Bicycle Platform",  
  journal = "Procedia Computer Science",  
  volume = "134",  
  pages = "464 - 469",  
  year = "2018",
```

```
note = "The 15th International Conference on Mobile Systems and  
Pervasive Computing (MobiSPC 2018) / The 13th International Conference on  
Future Networks and Communications (FNC-2018) / Affiliated Workshops",  
issn = "1877-0509",  
doi = "https://doi.org/10.1016/j.procs.2018.07.182",  
url =  
"http://www.sciencedirect.com/science/article/pii/S1877050918311475",  
author = "YeongKyun Lee and Jongpil Jeong",  
keywords = "Remote monitoring, Wireless sensor network, Smart phone  
based monitoring, Bicycle monitoring",  
abstract = "This paper proposes the smart phone as a central monitoring  
device for the bicycle and the WIFI network as a communication channel  
between the smart phone and the sensors. It will show how to implement the  
sensor boards with WIFI and relevant firmware, the software on the smart  
phone to communicate with the sensor boards and the evaluation results with  
the open source software called Goldencheetah. The knowledge in this paper  
is not limited to bicycles but can be expanded to any other monitoring  
systems using the remote sensors based on smart phone."  
}
```

```
@article{RANJITH2020,  
title = "Prediction of Exhaust Gas Emission characteristics using Neem  
oil blended bio- diesel in diesel engine",  
journal = "Materials Today: Proceedings",  
volume = "21",  
pages = "870 - 875",  
year = "2020",  
note = "International Conference on Recent Trends in Nanomaterials for  
Energy, Environmental and Engineering Applications",  
issn = "2214-7853",  
doi = "https://doi.org/10.1016/j.matpr.2019.07.706",  
url =  
"http://www.sciencedirect.com/science/article/pii/S2214785319329116",  
author = "Ranjith and V. Velmurugan and S. Thanikaikarasan",  
keywords = "Accelerometer, Diesel engine, Neem oil, Renewable,  
Alternative, Viscosity, Volatility",  
abstract = "As a renewable, sustainable and alternative fuel for diesel  
engine, biodiesel instead of diesel has been increasingly fuelled to study  
its effects on engine performances and emissions. Biodiesel production is a  
modern and technological area for researchers due to constant increase in  
the prices of petroleum, diesel, and environmental advantages. Increased  
environmental awareness and depletion of resources are driving industry to  
develop viable alternative fuels from renewable resources that are  
environmentally more acceptable. Neem oil is a potential alternative fuel.  
The most detrimental properties of neem oils are its high viscosity and low  
volatility, and these cause several problems during their long duration  
usage in diesel engines. From the review it is found that the use of  
biodiesel leads to the substantial reduction in CO2, HC, CO and NOx  
emissions."  
}
```

```
@article{SOBHANI2018,  
  title = "Impact of smartphone distraction on pedestrians crossing  
behaviour: An application of head-mounted immersive virtual reality",  
  journal = "Transportation Research Part F: Traffic Psychology and  
Behaviour",  
  volume = "58",  
  pages = "228 - 241",  
  year = "2018",  
  issn = "1369-8478",  
  doi = "https://doi.org/10.1016/j.trf.2018.06.020",  
  url =  
"http://www.sciencedirect.com/science/article/pii/S1369847818300998",  
  author = "Anae Sobhani and Bilal Farooq",  
  keywords = "Head-mounted immersive virtual reality, Pedestrian,  
Distracted street crossing, Multi-tasking, Smartphone use, Surrogate  
analysis, Smart LED lights safety treatment",  
  abstract = "A novel head-mounted virtual immersive/interactive reality  
environment (VIRE) is utilized to evaluate the behaviour of participants in  
three pedestrian road crossing conditions while 1) not distracted, 2)  
distracted with a smartphone, and 3) distracted with a smartphone with a  
virtually implemented safety measure on the road. Forty-two volunteers  
participated in our research who completed thirty successful (complete  
crossing) trials in blocks of ten trials for each crossing condition. For  
the two distracted conditions, pedestrians are engaged in a maze-solving  
game on a virtual smartphone, while at the same time checking the traffic  
for a safe crossing gap. For the proposed safety measure, smart flashing and  
color changing LED lights are simulated on the crosswalk to warn the  
distracted pedestrian who initiates crossing. Surrogate safety measures as  
well as speed information and distraction attributes such as direction and  
orientation of participants head were collected and evaluated by employing a  
Multinomial Logit (MNL) model. Results from the model indicate that females  
have more dangerous crossing behaviour especially in distracted conditions;  
however, the smart LED treatment reduces this negative impact. Moreover, the  
number of times and the percentage of duration the head was facing the  
smartphone during a trial and a waiting time respectively increase the  
possibility of unsafe crossings; though, the proposed treatment reduces the  
safety crossing rate. Hence, our study shows that the smart LED light safety  
treatment indeed improves the safety of distracted pedestrians and enhances  
the successful crossing rate."  
}
```

```
@article{OBAYASHI2020,  
  title = "Pilot and Feasibility Study on Elderly Support Services Using  
Communicative Robots and Monitoring Sensors Integrated With Cloud Robotics",  
  journal = "Clinical Therapeutics",  
  year = "2020",  
  issn = "0149-2918",  
  doi = "https://doi.org/10.1016/j.clinthera.2020.01.001",  
  url =  
"http://www.sciencedirect.com/science/article/pii/S0149291820300278",  
  author = "Kazuko Obayashi and Shigeru Masuyama",
```

keywords = "activities of daily living, cloud robotics, communicative robot, elderly care, robotics utilization, support services",

abstract = "Purpose

This pilot before-after study investigated the possible effects of communicative robots, used with a sensing system supported by cloud robotics, in caring for elderly people.

Methods

Two elderly women in nursing homes and 4 care workers participated in the trial. The overnight life rhythm assessments of the study participants and care workers were surveyed to determine when and how the robots should be integrated into care. The system consisted of the robot Sota, a noncontact vital sensor and a sheet-shaped bed sensor. Real-time sensing data and conversations between the participants and robots were sent to the servers, prompting a quick verbal response by the robot supported by cloud robotics.

Findings

Care workers devoted 3 h to the maintenance of records during their most stressful periods. Automatic recording of vital information using robot sensors can improve the quality of nursing care work. Care workers' stress levels were maximized when responding to nurse calls. Temporary responses to nurse calls by the robots may help to effectively reduce the burden on nursing care workers. Robots can stimulate elderly people to communicate more with others ($P < 0.05$). Appropriate vocalization by communicative robots may prevent the deterioration of quality of life in elderly individuals.

Implications

Communicative robots, used with a sensing system, may stimulate elderly people to activate a communication link with others and help care workers to effectively reduce the burden during the night shift. A follow-up study involving a broader research program on communicative robots and elderly care would be beneficial."

}

@article{THAPA2019,

title = "Study on the wintry thermal improvement of makeshift shelters built after Nepal earthquake 2015",

journal = "Energy and Buildings",

volume = "199",

pages = "62 - 71",

year = "2019",

issn = "0378-7788",

doi = "https://doi.org/10.1016/j.enbuild.2019.06.031",

url =

"http://www.sciencedirect.com/science/article/pii/S0378778819306309",

author = "Rita Thapa and Hom Bahadur Rijal and Masanori Shukuya and Hikaru Imagawa",

keywords = "Nepal, Earthquake, Temporary shelters, Indoor air temperature, Thermal insulation, Thermal improvement",

abstract = "After massive earthquake 2015, thousands of Nepalese who lost their permanent houses by the hardest hits were forced to live in makeshift temporary shelters. The field measurement on indoor thermal

environment in five shelters was conducted in one of the district hit by the earthquake, Lalitpur, in winter. The mean indoor and outdoor air temperatures during the measured nighttime were found to be 10.3 °C and 7.6 °C, respectively, and the nocturnal indoor air temperature remained below the lowest acceptable temperature of 11 °C. This result assured that these shelters are not good for winter and must create various problems. We therefore analyzed the thermal characteristics of those shelters based on the measured results in order to seek a possible improvement. The total heat loss coefficient estimated per floor area in five shelters ranged from 11.3 to 15.2 W/(m²·K); that is thermal insulation was very low. We made a simple numerical analysis on the variation of indoor air temperature with the assumption of improved thermal characteristics and thereby found that it needs to be reduced about 2~7 W/(m²·K) to have the indoor air temperature higher than 11 °C for 70\% of the whole nocturnal hours. Such reduction of heat loss was found to be realized by adding affordable materials, e.g., cellular polyethylene foam and clothes for respective walls and roof. Thus, the knowledge obtained from this study should hopefully be applied to actual improvement of indoor thermal environment in existing shelters and also to a development for the preparation against future disaster."

```

}

@MISC{gartner2021,
  author = "{Gartner}",
  title = "{Gartner Magic Quadrant for Data Science and Machine Learning Platforms}",
  url = "{https://www.gartner.com/en/documents/3998753}",
  urldate = "{March 2021}",
  year = "{2021}",
  address = "{[Accessed in April 2021]}",
}

@MISC{android41,
  author = "{Android Open Source Project}",
  title = "{Android Developers: Android 4.1 APIs}. January 2015. [Accessed in April, 2017]",
  url =
"{http://developer.android.com/about/versions/android-4.1.html}",
  urldate = "{May 2014}",
  year = "{2014}",
  address = "{[Accessed in April 2017]}",
}

@MISC{cloudexpo2008,
  AUTHOR = "{Cloud Expo}",
  title = "{Twenty-One Experts Define Cloud Computing}",
  url = "{http://cloudcomputing.sys-con.com/node/612375}",
  urldate = "{October 2013}",
  year = "{2008}",
  address = "{[Accessed in April 2021]}",
}

```

```
@BOOK{bandyopadhyay2013unsupervised,  
  title={Unsupervised Classification: Similarity Measures, Classical and  
  Metaheuristic Approaches, and Applications},  
  author={Bandyopadhyay, Sanghamitra and Saha, Sriparna},  
  year={2013},  
  isbn={978-3-642-32450-5},  
  publisher={Springer},  
  address = {Berlin, Germany},  
  doi = {10.1007/978-3-642-32451-2}  
}  
  
@ARTICLE{llorente2009virtual,  
  author  = "{Sotomayor, B. and Montero, Ruben S. and Llorente, I.M. and  
  Foster, I.}",  
  journal = "Internet Computing, IEEE",  
  title   = "{Virtual Infrastructure Management in Private and Hybrid  
  Clouds}",  
  year    = "{2009}",  
  month   = "{Sept}",  
  volume  = "{13}",  
  number  = "{5}",  
  pages   = "{14-22}",  
  abstract = {One of the many definitions of "cloud" is that of an  
  infrastructure-as-a-service (IaaS) system, in which IT infrastructure is  
  deployed in a provider's data center as virtual machines. With IaaS clouds'  
  growing popularity, tools and technologies are emerging that can transform  
  an organization's existing infrastructure into a private or hybrid cloud.  
  OpenNebula is an open source, virtual infrastructure manager that deploys  
  virtualized services on both a local pool of resources and external IaaS  
  clouds. Haizea, a resource lease manager, can act as a scheduling back end  
  for OpenNebula, providing features not found in other cloud software or  
  virtualization-based data center management software.},  
  doi = {10.1109/MIC.2009.119}  
}  
  
@article{Mulder2013428,  
  title = "Development of a Motion System for an Advanced Sailing  
  Simulator ",  
  journal = "Procedia Engineering ",  
  volume = "60",  
  number = "0",  
  pages = "428 - 434",  
  year = "2013",  
  note = "6th Asia-Pacific Congress on Sports Technology (APCST) ",  
  issn = "1877-7058",  
  doi = "http://dx.doi.org/10.1016/j.proeng.2013.07.030",  
  url =  
  "http://www.sciencedirect.com/science/article/pii/S1877705813010813",  
  author = "Fabian A. Mulder and Jouke C. Verlinden",  
  keywords = "Sailing",
```

```
keywords = "Dinghy",  
keywords = "Virtual reality",  
keywords = "Training simulation",  
keywords = "Force feedback",  
abstract = "Abstract To train competitive sailing in a virtual setting,  
motion of the boat as well as haptic feedback of the sail lines is  
essential. When discussing virtual environments (VEs) the concept of  
presence is often used. In this study we develop a sailing simulator motion  
system to research what factors contribute to the participants' sensation of  
presence when sailing in a VE. The developed simulator includes the  
development of a mainsheet force feedback system and a novel motion  
platform, connected to a high-quality graphics sailing simulation. In future  
research, the developed system will be used to study which sail training  
type can be performed in simulated environments, and if the system can be  
used as a valid testbed for perception-action experiments."  
}
```

From:

<https://www.mads4e.dee.isep.ipp.pt/> - **MADS4Engineering**

Permanent link:

<https://www.mads4e.dee.isep.ipp.pt/doku.php?id=refnotes:bib&rev=1652650108>

Last update: **2026/07/07 18:15**

